

13.9.3 T.30 PROTOCOL LIST**A. Use**

- Print out T.30 or V8 protocol after communication.
 - SESSION: Session number
 - FUNCTION: Function name
 - DESTINATION STATION: Destination Name/Tel. No.
 - DATE/TIME: Communication Date & Time
 - PAGE: Total page number for this session
 - DURATION: Communication using time
 - MODE: Communication speed and ECM mode
 - RESULT: Communication result
 - RING: Recording ring ON/OFF time by “ms”
 - Only for RX function and record last 16 time
 - TX: T.30 command sent by local fax
 - RX: T.30 command received from remote fax
 - DATA: T.30 frame that include address & control & data

B. Procedure

1. Enter the [SERVICE MODE].
2. Select [REPORT] and press the Select key.
3. Select [T.30 PROTOCOL LIST] and press the Select key.

(2) V.34 communication (example)

PROTOCOL MONITOR REPORT

NAME:TMFP
 TEL :886 3 4733507
 DATE:APR.10.2008 12:20

SESSION	FUNCTION	NO.	DESTINATION	STATION	DATE	TIME	PAGE	DURATION	MODE	RESULT
0001	TX	010	27187480		OCT.27	17:19	008	00h00min03s	ECM	OK

RING	DATA
ON Time (ms)	1200 1200 1200 1200 1200 1200 1200 1200 1200 1200 1200 1200 1200 1200 1200
OFF Time (ms)	3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000

TX	RX	DATA
	ANS	
CM	JM	V.8 PROTOCOL DUMP
CJ	NSF	FF 03 20 00 00 25 00 00 00 12 10 6D 02 00 58 00 28 B8 A4 A0 80 91 60
	NSF	FF 03 20 00 00 25 01 45 43 4E 45 59 45 4B
	CSI	FF 03 40 30 38 34 37 38 31 37 32 20 20 20 20 20 20 20 20
	DIS	FF 13 80 20 EE A8 C4 80 98 81 80 80 60
DCS	CFR	FF 13 83 00 02 F0 84 80 80 80 80 80 20
		FF 13 84
▶ PIX		
PPS-EOP	MCF	FF 13 BF 2F 00 00 7F
		FF 13 8C
DCN		FF 13 FB

A2YFF3C004DA

bizhub C25

ADJUSTMENT / SETTING

13.9.4 SERVICE REPORT

A. Use

- The report will generate and sending when toner empty happens and report request is set to "ON".

B. Procedure

1. Enter the [SERVICE MODE].
2. Select [REPORT] and press the Select key.
3. Select [SERVICE REPORT] and press the Select key.