

**FAX-JX500****Product Specification****Downloads**

Brochures  
Drivers

**Related Products**

Laser Faxes

<b>Type</b>	Standard Facsimile with Telephone Answering Machine and handset
<b>Compatibility</b>	Group 3
<b>Applicable line</b>	PSTN
<b>Print technology</b>	Inkjet Printing
<b>Scanner type</b>	Sheet fed
<b>Automatic document feeder</b>	20 sheets
<b>Document size</b>	Width: 216mm(Max) ~ 105mm(Min) Length: 400mm(Max) ~ 105mm(Min)
<b>Effective scanning width</b>	208mm
<b>Scanning speed</b>	10 seconds per page 6 pages per minute
<b>Fax resolution</b>	Fine: 8 dots x 7.7 lines / mm Standard: 8 dots x 3.85 lines / mm
<b>Image processing system</b>	UHQ (Ultra High Quality)
<b>Halftone</b>	256 shades of grey scale
<b>Printing method</b>	Inkjet Printing
<b>Print speed</b>	10 seconds per page 6 pages per minute
<b>Print resolution</b>	600 x 600 dpi
<b>Paper capacity</b>	100 sheets Auto Sheet Feeder
<b>Print cartridge</b>	PG-40 or PG-50 Black Cartridge (PG-40 included in box) PG-40 approx. 520 pages (using Canon Fax Standard Chart No.1) PG-50 approx. 800 pages (using Canon Fax Standard Chart No.1)
<b>Printing width</b>	203 mm
<b>Ink save mode</b>	Yes
<b>Auto image reduction on reception</b>	Yes
<b>Transmission speed</b>	Approx. 3 seconds per page (based on ITU-No.1 chart)
<b>Modem speed</b>	33.6 kbps
<b>Compression method</b>	MH, MR, MMR
<b>Direct transmission</b>	Yes
<b>Quick memory transmission</b>	Yes
<b>FAX memory</b>	Approx. 120 pages
<b>Memory backup</b>	Yes (FLASH memory)
<b>Error correction mode(ECM)</b>	Yes
<b>Delayed transmission</b>	Yes (110 locations)
<b>Sequential broadcast</b>	Yes (110 locations)
<b>Polling reception</b>	Yes

<b>Direct mail prevention</b>	Yes
<b>Reports and Lists</b>	Activity report, Transmission report, Reception report, Multi TX/RX reports, One-touch/Coded speed dialing list, User's data list, Doc. memory list
<b>Transmission header</b>	Yes
<b>One touch dials</b>	9 locations
<b>Coded dials</b>	100 locations
<b>Redial</b>	Yes (Automatic and Manual)
<b>FAX/TEL auto switch</b>	Yes
<b>Extension hook up</b>	Yes
<b>Remote reception</b>	Yes
<b>On hook key</b>	Yes
<b>Caller ID</b>	Yes <sup>1</sup>
<b>Telephone handset</b>	Yes
<b>Telephone handset Cradle</b>	Built in
<b>Built in answering machine</b>	Yes
<b>Type</b>	Digital
<b>Total recording time</b>	Approx. 30 minutes
<b>Number of messages</b>	50
<b>Max. time per message</b>	60/120/240 seconds (User Setting)
<b>OGM</b>	1 (max 20 secs)
<b>Remote operation</b>	Yes
<b>Time stamp</b>	Yes (LCD only)
<b>Message back up</b>	Yes
<b>Call screening</b>	Yes
<b>Toll Saver</b>	Yes
<b>Mono Copy</b>	Yes
<b>Copy resolution</b>	600x600 dpi
<b>Copy speed ( Mono )</b>	1.20 pages per minute (ITU-T No.1 chart, Fine mode) 48 seconds per page (ITU-T No.1 chart, Fine mode)
<b>Multiple copy</b>	Up to 99 copies
<b>Display Type</b>	LCD
<b>Display Size</b>	16x1
<b>Display Languages</b>	16 languages ( English, German, French, Spanish, Italian, Swedish, Norwegian, Dutch, Finnish, Danish, Portuguese, Slovenian, Czech, Hungarian, Russian, Polish )
<b>Dimensions W/O trays and handset(WxDxH)</b>	400 (W) x 269 (D) x 169 (H) mm
<b>Dimensions with trays and handset(WxDxH)</b>	400 (W) x 306 (D) x 294 (H) mm

<b>Weight</b>	Approx. 4.1 kg
<b>Power source</b>	AC 200-240V 50-60Hz
<b>Power consumption</b>	Approx. 1.5W (Sleep mode), approx. 37W (Max)

Caller ID	<sup>1</sup> To use this feature, you will need to subscribe for a Caller ID service (only available in some countries). The Caller ID feature uses the ETSI EN 300 778-1 protocol. Contact your local telephone company for detailed information on this service.
-----------	--

© Copyright 2007 | Terms and Conditions of use